

60 MINUTE FIRE RESISTIVE GLASS PRODUCTS COMPARISON IN WALLS, SIDELITES AND TRANSOMS

(See next page for *60 Minute Fire Resistive Glass Products Comparison in Doors*)

All products meet ASTM E-119/ULC 263/CAN-ULC S101 with hose stream and CPSC impact safety requirements.

FIRE RESISTIVE TEMPERED UNITS

60 Minute Fire Resistive Product	Origin	Appearance	Cost	Max. Area (sq. in.)	Warranty	Thickness/ Weight per sq. ft.	Custom Options
★ <i>BEST OPTION</i>							
SuperLite II-XL 60 by SAFTI <i>FIRST</i>	USA	Clear	\$\$\$	4,952 sq. in.	5 years	1-3/8 in. / 14 lbs.	Starphire Ultra-Clear by Vitro, Insulated, Low-E, Decorative, Hurricane, Forced Entry, Ballistic, Blast, X-Ray, etc.
SuperLite II-XLB 60 by SAFTI <i>FIRST</i>	USA	Clear	\$\$\$	10,000 sq. in.	5 years	1-7/8 in. / 17.7 lbs.	Starphire Ultra-Clear by Vitro, Insulated, Low-E, Decorative, Hurricane, Forced Entry, Ballistic, Blast, X-Ray, etc.
Contraflam 60 by Vetrotech	USA	Clear	\$\$\$\$	4,449 sq. in.	5 years	1 in. / 10.3 lbs.	Insulated, Low-E, Hurricane, Ballistic

FIRE RESISTIVE ANNEALED MULTILAMINATE

60 Minute Fire Resistive Product	Origin	Appearance	Cost	Max. Area (sq. in.)	Warranty	Thickness/ Weight per sq. ft.	Custom Options
SuperLite II-XLM 60 by SAFTI <i>FIRST</i>	Imported	Clear	\$\$\$\$	3,855 sq. in.	5 years	1 in. / 12.3 lbs.	Insulated
Pyrostop 60 by Pilkington	Imported	Clear	\$\$\$\$	5,605 sq. in.	5 years	7/8 in. / 11.3 lbs.	Insulated, Low-E, Decorative, Ballistic, X-Ray

60 MINUTE FIRE RESISTIVE GLASS PRODUCTS COMPARISON IN DOORS

(See previous page for *60 Minute Fire Resistive Glass Products Comparison in Walls, Sidelites and Transoms*)

All products meet ASTM E-119/ULC 263/CAN-ULC S101 with hose stream and CPSC impact safety requirements.

FIRE RESISTIVE TEMPERED UNITS

60 Minute Fire Resistive Product	Origin	Appearance	Cost	Max. Area (sq. in.)	Warranty	Thickness/ Weight per sq. ft.	Custom Options
★ <i>BEST OPTION</i>							
SuperLite II-XL 60 by SAFTI <i>FIRST</i>	USA	Clear	\$\$\$	4,952 sq. in.	5 years	1-3/8 in. / 14 lbs.	Starphire Ultra-Clear by Vitro, Insulated, Low-E, Decorative, Hurricane, Forced Entry, Ballistic, Blast, X-Ray, etc.
Contraflam 60 by Vetrotech	USA	Clear	\$\$\$\$	2,684 sq. in.	5 years	1 in. / 10.3 lbs.	Insulated, Low-E, Hurricane, Ballistic

FIRE RESISTIVE ANNEALED MULTILAMINATE

60 Minute Fire Resistive Product	Origin	Appearance	Cost	Max. Area (sq. in.)	Warranty	Thickness/ Weight per sq. ft.	Custom Options
SuperLite II-XLM 60 by SAFTI <i>FIRST</i>	Imported	Clear	\$\$\$\$	3,855 sq. in.	5 years	1 in. / 12.3 lbs.	Insulated
Pyrostop 60 by Pilkington	Imported	Clear	\$\$\$\$	3,724 sq. in.	5 years	7/8 in. / 11.3 lbs.	Insulated, Low-E, Decorative, Ballistic, X-Ray